

# Technical Information

Treatment Solution for Aluminum Foil and Aluminum Evaporation Paper

# GP AC No.3



GP AC No.3 primer is used for untreated aluminum foils, untreated aluminum laminated paper and aluminum evaporation paper. It excels in water resistance and provides excellent adhesiveness, especially to overprint UV inks. It is non-toluene halogen free polyester type primer

Main Resin	Polyester
Non-volatile Content	25±1%
Diluent	MEK : Ethyl acetate = 2 : 1
Normal Amount Of Coating	1 ± 0.2g/m2

#### ■Features

- · Excellent adhesion to overprint UV ink.
- Non-toluene
- Halogen free (resin composition does not contain chlorine).

### ■Applications

- · Untreated aluminum foil
- Untreated laminated paper
- · Aluminum evaporation paper

## Handling Instructions

- Adhesion varies depending on the type of UV ink. Consult us prior to use. Further, we will conduct confirmation tests if you send us your usage conditions.
- · Contact us if slow solvent is required.

- ▶ The data contained herein are based on the results of the tests conducted in accordance with the in-house test methods, and are not standard values. Always conduct pre-use tests to ascertain the suitability of the product to your requirements. Nothing contained herein is to be construed as a recommendation for use in violation of any patents, applicable laws or regulations. It is the responsibility of the user to comply in all respects with applicable laws and regulations
- Owing to product improvement the information contained herein may be modified without any prior notice.
- Make sure to read MSDS thoroughly before using the product.